

MORSUN SYNTHETIC NON-SKID DECK PAINT

PRODUCT CODE**MCS-AL-022****PRODUCT DESCRIPTION**

A high quality Non-Skid Deck Paint based on Synthetic Resins suitably pigmented and appropriately loaded with inert aggregates

SUGGESTED USES

An ideal paint to be used as final coating on the decks of marine vessels where weather resistance, durability and non-skid properties are expected

TECHNICAL DATA

Colour	Is limited, i.e. Deck Green & Dark Grey
Finish	Matt
Flash Point	> 30° C
Volume Solids	64% ±2
Recommended Dft	150 to 200μ (as the material is of textured finish exact film thickness cannot be measured)
Theoretical Spreading Rate	3.2 M ² /ltr. at 200μ
With 30% Loss	2.24 M ²
Drying Time	Surface Dry : 1 hour maximum
Hard Dry	Overnight
Overcoating Interval	24 hours minimum, No Maximum
Method of Application	Brush / Roller
Thinner Recommended	Morsun G. P. Thinner
Surface Preparation	Clean, dry and free from all contaminants, suitably primed
Packing	20 litres, 10 litres

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.