

MORSUN SYNTHETIC FLAT PAINT WHITE

PRODUCT CODE**MCS-AL-024****PRODUCT DESCRIPTION**

A high quality synthetic resin based matt finish paint

SUGGESTED USES

Ideal for use as finish paint in the interior area of ships viz. accommodation spaces, wheel house, dining rooms, etc

TECHNICAL DATA

Colour	White
Finish	Flat / Matt
Flash Point	> 30°C
Volume Solids	44% ±2
Recommended DFT	30 to 40μ
Theoretical Covering	11.0 M ² per ltr. at 40μ
With 30% Loss	7.7 M ² per ltr
Mode of Application	Brush / Roller / Airless /Con. Spray
Airless Spray	Tip Size: 0.018-0.024
Fluid Pressure	2000-3000 psi
Thinner	Morsun G. P. Thinner
Drying Time	Surface Dry : 1hour maximum
Hard Dry	Overnight
Overcoating Interval	24 hours, No Maximum
Surface Preparation	Surface should be clean, dry and free from all contaminants and suitably primed
Shelf Life	12 months
Packing	20 litres, 4 litres

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.