

MORSUN SYNTHETIC BOOT TOP FINISH

PRODUCT CODE**MCS-AL-028****PRODUCT DESCRIPTION**

A finishing paint based on Synthetic Resin medium

SUGGESTED USES

Recommended for use on Boot top Areas of ships and gives good gloss and salt-water resistance. To be used over Primer Red/Yellow /Grey

TECHNICAL DATA

Colour	Red/Black
Finish	Glossy
Flash Point	> 30°
Volume Solids	48% ±2
Recommended DFT	60μ
Theoretical Covering	8 M ² /ltr. at 60μ
With 30% Loss	5.6 M ²
Mode of Application	Brush / Roller / Airless/ Con. Spray
Airless Spray	Tip Size: 0.015"0.021"
Fluid Pressure	2000-2500 psi
Thinner	Morsun G. P. Thinner
Drying Time	Surface Dry : 1 hour maximum
Hard Dry	Overnight
Overcoating Interval	24 hours minimum, No Maximum
Surface Preparation	Surface should be clean, dry & free from all contaminants and suitably primed
Shelf Life	12 months
Packing	20 litres, 4 litres

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.