

MORSUN SYNTHETIC SEMI-GLOSS FINISH

PRODUCT CODE**MCS-AL-030****PRODUCT DESCRIPTION**

A semi-glossy finish paint based on synthetic resin

SUGGESTED USES

Ideal for use as finish paint in the interior area of ships viz. on decks and dados onboard ships

TECHNICAL DATA

Colour	As required
Finish	Semi-Glossy
Flash Point	> 30°C
Volume Solids	44% ±2
Recommended DFT	25 to 30μ
Theoretical Covering	17.6 M ² per ltr. at 25μ
With 30% Loss	12.3 M ² per ltr
Mode of Application	Brush / Roller / Airless /Con. Spray
Airless Spray	Tip Size: 0.015"-0.021"
Fluid Pressure	2000-3000 psi
Thinner	Morsun G. P. Thinner
Drying Time	Surface Dry : 1hour maximum : Hard Dry : Overnight
Overcoating Interval	24 hours, No Maximum
Surface Preparation	Surface should be clean, dry and free from all contaminants and suitably primed
Shelf Life	12 months
Packing	20 litres, 4 litres

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.