

MORSUN SYNTHETIC SURFACE TOLERANT BOTTOM PRIMER

PRODUCT CODE

MCS-AL-043

PRODUCT DESCRIPTION

A single pack Quick Drying Primer ideal for use on exterior hull of ships from bottom to boot top area and deck area. It ensures excellent corrosion resistance of the hull and provides a suitable base for the subsequent topcoats of C.R. and Alkyd systems

SUGGESTED USES

As an Anti-corrosive primer on manually prepared outer hull of ships including bottom, boot-top and main deck area

TECHNICAL DATA

Colour	Grey
Finish	Glossy
Flash Point	> 25°C
Volume Solids	38% ±2
Recommended DFT	35 - 40μ
Covering Capacity	9.5 M ² /ltr. at 40μ
With 30% Loss	6.65 M ² /ltr
Method of Application	Brush/Roller
Thinner Recommended	Morsun C.R. Thinner
Drying Time	Surface Dry : 20 – 30 mts
Hard Dry	6 – 8 hrs
Overcoating Interval	Minimum 8 – 10 Hours
Surface Preparation	Prepare the surface manually / mechanically by tooling, chipping, wire brushing, etc. to ST2. Ensure the surface is free from all contaminants like oil, grease, dust, rust, etc. prior to application of primer
Shelf Life	12 Months
Packing	4 Litres, 20 Litres
Limitation	This paint is not resistant to Oils, Grease & Fats and is liable to soften and decompose above 60°C
Precautions	Ventilate the area to be painted thoroughly to avoid suffocation while application

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.