

SYNTHETIC MARKING PAINT FOR PACKAGES & PETROL CONTAINERS (CONFORMING TO IS-138)

PRODUCT CODE**MCS-AL-046****PRODUCT DESCRIPTION**

A superior quality quick drying marking paint based on Synthetic Resin and weather resistant pigments. Product conforms to IS – 138

SUGGESTED USES

Recommended for use as a Marking Paint for Packages and Petrol Containers

TECHNICAL DATA

Colour	As required from IS-5
Finish	Smooth Semi-glossy to Matt as required
Solid Volume	44% ±2
Flash Point	Min 30° C
Recommended DFT	50μ
Theoretical Covering	9.6 M ² per ltr. at 50μ
With 30% Loss	6.0 M ² per ltr
Mode of Application	Brush or Suitable Marking Application
Thinner Recommended	Morsun G. P. Thinner
Drying Time	Hard Dry : 2 Hours Max
Viscosity by Ford Cup B-4	80 to 120 seconds as per IS-101
Performance as per IS-101	Resistant to (1) Lubricating oil (2) Water (3) Petroleum Hydrocarbon
Surface Preparation	Surface should be free from all contaminants dry
Shelf Life	12 months
Packing	20 litres, 4 litres

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.