

MORSUN SYNTHETIC ENAMEL INTERIOR UNDERCOATING FINISH PAINT (CONFIRMING TO IS-133)

PRODUCT CODE**MCS-AL-049****PRODUCT DESCRIPTION**

It is high quality synthetic based product having excellent adhesion and finish coat paint

SUGGESTED USES

This is finishing coat product used for decorating and protection of interior surface and is normally applied as painting system as an appropriate primer followed by finish topcoat paint. It has a high gloss finish with good durability

TECHNICAL DATA

Colour	All Shades
Finish	Smooth and Glossy
Gloss	Above 71 units
Volume Solids	34 ± 2 %
Recommended dft	35-40 µ
Theoretical Covering	10 M2 at 35 µ
Method of Application	Brush / Roller for small area, Conventional/ Airless spray for bigger areas
Heat Resistance	Upto 60°C dry heat (Intermittently)
Thinner Recommended	Sunthane Thinner
Airless Spray	Tip size: 0.015"- 0.019" : Fluid pressure: 2000- 2500 psi
Drying Time	Surface Dry : 4 hours
Tack Free	12 hours
Hard Dry	24 hours
Flash Point	30 deg C
Overcoating Interval	16 hours
Shelf Life	12 months in sealed container stored at room temperature
Packing	20 litres, 4 litres
Precautions	Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.