

MORSUN SYNTHETIC ENAMEL EXTERIOR WHITE PRIMER

PRODUCT CODE

MCS-AL-057

PRODUCT DESCRIPTION

A best quality alkyd-based primer designed to surfaces uniformly, fast dry excellent adhesion. Ideal use in decorating and protection and provides good corrosion protection on metal surfaces

SUGGESTED USES

its use in exterior surfaces such as new or previously painted Metal, steel wood, masonry, and brick. For application in commercial and residential areas

TECHNICAL DATA

Colour	White
Finish	Smooth Matt
Gloss	0-10 unit
Volume Solids	50 ± 2 %
Recommended dft	38-45 µ
Theoretical Covering	11.20 M2 at 45µ
Method of Application	Brush / Roller for small area, Conventional/ Airless spray for bigger areas
Heat Resistance	Upto 60°C dry heat (Intermittently)
Thinner Recommended	Sunthane Thinner
Airless Spray	Tip size: 0.015"- 0.019" : Fluid pressure: 2000- 2500 psi
Drying Time	Surface Dry : 1-2 hours
Tack Free	4-6 hours
Hard Dry	24 hours
Flash Point	30 deg C
Overcoating Interval	24 hours
Shelf Life	12 months in sealed container stored at room temperature
Packing	20 litres, 4 litres
Precautions	Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.