

MORSUN H.B. BITU BLACK

PRODUCT CODE
MCS-BT-601
PRODUCT DESCRIPTION

A high build anti-corrosive black paint based on bitumen medium containing phenolic resin suitably pigmented

SUGGESTED USES

An economical Anticorrosive coating for ballast tank, cofferdam area, cable locker, anchor, anchor-chain, beneath insulation, etc. onboard ship

TECHNICAL DATA

Colour	Black
Finish	Semi glossy
Solids Volume	50% + 2
Recommended DFT	100μ
Theoretical Covering	10M2 @ 50μ per coat
With 30% Loss	7M2/Litre @ 50μ
Drying Time	Surface Dry : 4 - 6 hours
Hard Dry	24-48 hours
Overcoating Interval	24 hours minimum at normal atmospheric conditions. No maximum
Thinner	G.P. Thinner
Mode of Application	Brush/Roller/Airless Spray
Airless Spray	Tip Size : 0.018" – 0.024" : Fluid Pressure : 2500 – 3000 psi
Surface Preparation	Manually / mechanically to ST 2 suitably primed
Shelf Life	Upto 9 months so long as the material is stored in sealed containers under standard warehouse storage conditions at room temperature
Precautions	Ventilate confined spaces adequately while painting
Packing	20 Litres

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.