

MORSUN RMP BRUSHING BITUMINOUS BLACK PAINT IS-9862

PRODUCT CODE**MCS-BT-604****PRODUCT DESCRIPTION**

This material is Ready mixed paint, brushing unpigmented bituminous base paint. It provides good adhesion and durability

SUGGESTED USES

This material is used for the paint of drinking water tank. Application for painting of funnel, boiler, apparatus, equipment machines

TECHNICAL DATA

Colour	Black
Finish	Smooth & Eggshell to Semi-Glossy
Gloss	7-35 unit
Solids By weight, Min	45 %
Recommended dft	35-40 µ
Theoretical Covering	10 M2 at 35 µ
Method of Application	Brush / Roller for small area, Conventional/ Airless spray for bigger areas
Heat Resistance	Upto 60°C dry heat (Intermittently)
Thinner Recommended	GP Thinner
Airless Spray	Tip size: 0.015"- 0.019" : Fluid pressure: 2000- 2500 psi
Drying Time	Surface Dry : 2-3 hours
Tack Free	8-10 hours
Hard Dry	24 hours
Flash Point	30 deg C
Overcoating Interval	18 hours
Shelf Life	12 months in sealed container stored at room temperature
Packing	20 litres, 4 litres
Precautions	Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.