

MORSUN EPOXY STOVING FINISH

PRODUCT CODE

MCS-EF-271

PRODUCT DESCRIPTION

A specially designed single pack Epoxy: Stoving Finis Paint for application on suitably primed metallic substrates. Application of adequate no of coats of primer and finish and stoving as per schedule it provides a smooth semi-glossy finish with excellent anti-corrosive properties

TECHNICAL DATA

Colour	As Required
Finish	Semi-Glossy
Flash Point	> 25° C
Volume Solids	46% ± 2
Recommended DFT	30 µ per coat
T.C.C	15.3 M ² /ltr. at 30 µ
With 10% Loss	10.7 M ²
Method of Application	Con. Spray
Stoving Schedule	120° - 130°C for 30 / 20 minutes (Allow flash-off time of 10 - 15 minutes before stoving)
Recommended Thinner	Morsun Epoxy Stoving Thinner
Shelf Life	12 Months in sealed containers under room temperature
Surface Preparation	Surface should be thoroughly cleaned, free from all contaminants and suitably primed
Packing	20 Litres, 4 litres

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.