

MORSUN EPOXY SURFACER (TWO PACK) IS:13239

PRODUCT CODE

MCS-EP-241

PRODUCT DESCRIPTION

Morsun Epoxy Surfacers is a two-component epoxy surfacer cured with polyamide applied on Epoxy Primer. It is highly pigmented and easy to sand and good adhesion to composite

SUGGESTED USES

The material is intended to be used as a surfacer over an epoxy based primed surface and mastic filler for the protection of exterior. The material shall be used after the surface imperfections are well covered with a two-component epoxy mastic filler. The surfacer is used with the object of getting a smooth, uniform and non-absorbent base for the finishing enamel. It provides good compatibility with two pack, polyurethane enamel, two pack epoxy based primer and mastic filler. Suitable for use on metal, wood, masonry etc

TECHNICAL DATA

Colour	White or as agreed
Finish	Matt to Eggshell
Gloss	0- 20 unit
Volume Solids, Minimum	42 ± 2 %
Recommended dft. Minimum	40 µ
Theoretical Covering	10.50 M2 at 40 µ
Method of Application	Brush / Roller for small area, Conventional/ Airless spray for bigger areas
Heat Resistance	Upto 120 °C dry heat (Intermittently)
Thinner Recommended	Sunthane Thinner
Airless Spray	Tip size: 0.015"- 0.019" : Fluid pressure: 2000- 2500 psi
Drying Time	Surface Dry : 4 hours
Tack Free	12 hours
Hard Dry	24 hours
Flash Point	24 deg C Pot Life, 27±2 deg C, Minimum : 4 Hours
Overcoating Interval	16 hours
Shelf Life	12 months in sealed container stored at room temperature
Packing	20 litres, 4 litres
Precautions	Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.