

MORSUN ALUMINIUM WATER RESISTANT PAINT TO IS 3585

PRODUCT CODE**MCS-NS-705****PRODUCT DESCRIPTION**

It is Ready Mixed Paint (RMP) is used as a primer in the Painting System normally for Paints and Wooden Surface. It is used for the protection of Woodwork both under marine and inland outdoor conditions. It may also used for direct application to metal surface

TECHNICAL DATA

Drying Time	Hard Dry : 6 Hours Max
Consistency Time of Flow	Smooth and Uniform 30 – 40 Seconds
Finish	Smooth
Scratch Hardness	No Such Scratch as to show bare Metal
Flex and Adhesion After	No Visible damage or detachment of film. 48 Hours Air Dry
Protection Against	No Sign of Corrosion. Corrosion Under Conditions of Condensation
Wt/Ltr (Min)	9.2 Kg / 10 Ltrs
Flash Point	Not below 30* C
Keep Properties	1 Year
Lead Content	Lead Free (Not more than 0.30%)
Packing	20 Ltrs. / 4 Ltrs

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.