

MORSUN RFU DEAD BLACK TO JSS:8010-31

PRODUCT CODE

MCS-NS-718

PRODUCT DESCRIPTION

This paint material is consist of high quality synthetic resin which satisfying the requirement. It is single pack and high build

SUGGESTED USES

Matt Black is a fast-drying matt finish for quick and easy application for metal protection and beautification of primed steel. A suitable clear top-coat can be painted to protect black matt for exterior weather-ability

TECHNICAL DATA

Colour	Black
Finish	Smooth and Matt
Gloss	0-10 Unit
Volume Solids	48 ± 2 %
Recommended dft	40-50 µ
Theoretical Covering	12 M2 at 40 µ
Method of Application	Brush / Roller for small area, Conventional / Airless spray for bigger areas
Heat Resistance	Upto 60°C dry heat (Intermittently)
Thinner Recommended	Sunthane Thinner
Airless Spray	Tip size: 0.015"- 0.019" : Fluid pressure: 2000- 2500 psi
Drying Time	Surface Dry : 20-30 minutes
Tack Free	2-3 hours hours
Hard Dry	24 hours
Flash Point	24 deg C
Overcoating Interval	16 hours
Shelf Life	12 months in sealed container stored at room temperature
Packing	20 litres, 4 litres
Precautions	Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.