

MORSUN ENAMEL MATT FINISH PAINT (PAINT CONFIRMING TO JSS 8010-54)

PRODUCT CODE**MCS-NS-727****PRODUCT DESCRIPTION**

It is based on high quality alkyd resin which forms tough film and provides excellent adhesion and durability

SUGGESTED USES

It is deal in use for interior surface like metal, wood, cement plaster, concrete and steel surfaces. It gives smooth and matt finish

TECHNICAL DATA

Colour	White, Off White or as agreed
Finish	Smooth and Matt
Gloss	0-10 unit
Volume Solids	45 ± 2 %
Recommended dft	35-40 µ
Theoretical Covering	10 M2 at 45 µ
Method of Application	Brush / Roller for small area, Conventional/ Airless spray for bigger areas
Heat Resistance	Upto 60°C dry heat (Intermittently)
Thinner Recommended	Sunthane Thinner
Airless Spray	Tip size: 0.015"- 0.019" : Fluid pressure: 2000- 2500 psi
Drying Time	Surface Dry : 2-3 hours
Tack Free	8 hours
Hard Dry	24 hours
Flash Point	30 °C
Overcoating Interval	16 hours
Shelf Life	12 months in sealed container stored at room temperature
Packing	20 litres, 4 litres
Precautions	Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.