

MORSUN COLD MARKING PAINT

PRODUCT CODE

MCS-SC-503

PRODUCT DESCRIPTION

Single Pack Cold Marking Paint based on Specialty binder, and Heat Resistant Pigment

SUGGESTED USES

Air Drying Marking Paint for Metal Surfaces with excellent hiding. This Paint can be used by automatic robotic marking machine Paint is heat resistant up to 450 to 500 degree centigrade

TECHNICAL DATA

Colour	White Opaque
Finish	Matt
Viscosity FC B-4 Cup	22 to 25 Seconds
Solids	38 +/- 2% by weight 21 +/- 2% by Volume
VOC	625 gms/Ltr
Approx. Recommended dft	10 – 15 μ
Method of Application	For classic Dot paint or Single Nozzle Application
Substrate	Iron or Steel
Thinner Recommended	Thinner for Cold Marking Paint
Pot Life	Not applicable (Not a 2K Paint) Unused Paint After application should be Covered. However application systems and Pipeline should be flushed with recommended Thinner
Drying Time	Surface Dry : 15 Minutes
Tack Free	15 Minutes
Hard Dry	20 Minutes
Special Instruction	Stir well and strain through 40 mesh sieve before using it. After application connected Robotic machine and lines to this product till Machine line is free from Paint
Flash Point	11 Degree Centigrade
Shelf Life	12 months in sealed container stored at room temperature 30° C under shed
Packing	20 KG, 4 KG
Precautions	Take necessary precautions to avoid contact with skin or eyes

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.