

MORSUN HOT MARKING PAINT – SOLVENT BORNE

PRODUCT CODE

MCS-SC-504

PRODUCT DESCRIPTION

Single Pack Hot Marking Paint based on Specialty binder, Heat Resistant Pigment and Aromatic Solvent. Cured film has sufficient hardness, flexibility and Ant-corrosive properties

SUGGESTED USES

Hot Marking Paint for Metal Surfaces with excellent hiding. This Paint can be used for 500 to 650 degree centigrade surface temperature range

TECHNICAL DATA

Colour	White
Finish	Matt
Viscosity FC B-4 Cup	20 to 30 Seconds
Solids	60% +3
Solvent Content	40% +3
Approx. Recommended dft	15 – 25 μ
Method of Application	For classic Dot paint or Single Nozzle Application
Substrate	Iron or Steel
Substrate Temperature Range	Between 500 - 650°C
Thinner Recommended	Thinner for Hot Marking Paint
Special Instruction	Stir well before using
Flash Point	> 35° C
Shelf Life	12 months in sealed container stored at room temperature 30° C
Packing	20 kgs., 4 kgs

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.