

MORSUN SYNTHETIC OR OIL BASED PUTTY IS-419

PRODUCT CODE**MCS-SC-506****PRODUCT DESCRIPTION**

This material mainly consists of synthetic varnish or oil which formed a smooth paste with mineral extenders

SUGGESTED USES

This is putty in paste form, which is applicable for the application of window frames and metal surfaces. It has good adhesion and smooth finishes, and it can be coated with synthetic finishes

TECHNICAL DATA

Colour	White, Off White or as agreed
Finish	Smooth and pasty
Gloss	Matt finish
Residue on sieve by weight, Max	5 %
Water Content by Weight, Max	15 %
Method of Application	Putty Knife /Spatula
Thinner Recommended	GP Thinner (If required)
Drying Time	Surface Dry : 2hours
Tack Free	8 hours
Hard Dry	24 hours
Flash Point	30 deg C
Overcoating Interval	24 hours
Shelf Life	Min 6 months in sealed container stored at room temperature
Packing	20 Kgs, 5 Kgs
Precautions	Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.