

MORSUN HAMMER TONE FINISH PAINT

PRODUCT CODE

MCS-SC-511

PRODUCT DESCRIPTION

This product is based on special and fast drying of resin which exhibit hammer pattern and hammer finishes

SUGGESTED USES

Ideal use for industrial finishes for interior and exterior. Quick drying with excellent hammer finish. Recommendd use in finish on metal finishes, machinery, office equipment, tool boxes lab instruments, trailers etc

TECHNICAL DATA

Colour	Silver or tinted colours
Finish	Glossy
Gloss	Above 71 units
Volume Solids	30 ± 2 %
Recommended dft	20-25 µ
Theoretical Covering	10 M2 at 30 µ
Method of Application	Brush / Roller for small area, Conventional/ Airless spray for bigger areas
Heat Resistance	Upto 60°C dry heat (Intermittently)
Thinner Recommended	Sunthane Thinner
Airless Spray	Tip size: 0.015"- 0.019" : Fluid pressure: 2000- 2500 psi
Drying Time	Surface Dry : 10-20 Minutes
Tack Free	1-2 hours
Hard Dry	24 hours
Flash Point	24 deg C
Overcoating Interval,Minimum	2 hours
Shelf Life	12 months in sealed container stored at room temperature
Packing	20 litres, 4 litres
Precautions	Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.