

MORSUN SYNTHETIC QUICK DRYING CLEAR VARNISH

PRODUCT CODE**MCS-VR-624****PRODUCT DESCRIPTION**

Single pack Anti-corrosive Clear Varnish based on Modified Synthetic Resin suitable for exterior use

TECHNICAL DATA

SUGGEST USES	An ideal coating to be used as a finish coat on a variety of substrates, viz, Wood, Ferrous and Non-Ferrous substrates. The cured film provides highly transparent hard, flexible, abrasion and stain resistant coating which has excellent anti-corrosive property and durability
Colour	Clear
Finish	Glossy
Volume Solids	40% ±2
Weight Solids	48% ±2
Mixing Ratio (By volume)	Single Pack
Recommended dft	15 – 20 mic
Theoretical Covering	20.0 M ² /ltr. at 20 mic
Method of Application	Brush / Roller / Conventional Spray
Thinner Recommended	Thinner for QD Varnish. No other thinner should be used
Drying Time	Handleable in 10-15 Minutes and hard dries also fast, subject to ambient temperature and DFT .Lower DFT gives faster DRYING
Surface Preparation	Ensure application is carried out on a clean and dry surface free of all contaminants viz. oil, grease, rust, dust, etc
Shelf Life	12 months in sealed container stored at room temperature
Packing	20 liters, 4 liters
Precautions	Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area. Store this Varnish under roof in cool & well-ventilated room

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.