

MORSUN FIRE RETARDANT CLEAR LACQUER

PRODUCT CODE

MCS-VR-626

PRODUCT DESCRIPTION

Morsun Fire Retardant Clear Lacquer is based on Syn. Resin and Fire Retardant Pigments. It is recommended for use on wooden surfaces. It is suitable for use on Ship's Bulkheads and other Fire Prone areas as a Protective and Fire Retardant Coating which will not propagate fire due to transmission of heat through metal work. This Fire Retardant Coating provides 1. Excellent insulation to the coated substrate against fire. 2. Flexible non-sagging coating. 3. Good protection to steel surfaces against corrosion. 4. Excellent application properties. Fire Retardant Coating is mainly used in the interior of buildings, exterior surfaces of combustible structures, the below deck area on board ships where heat insulation is provided and the lagging which covers the insulation material

TECHNICAL DATA

Colour	Transparent
Finish	Smooth Semi-glossy
Flash Point	> 30°C
Volume Solids	35% + 2
Recommended Dft	20 to 25µ per coat
Theoretical Spreading	15 M2 @ 25µ
With 30% Loss	7.0 M2 @ 25µ
Mode of Application	Brush / Spray
Drying Time	Surface Dry : 3 to 4 hours
Hard Dry	Not over 8 hours
Overcoating Interval	8 hours min. No Maximum
Thinner Recommended	Not required
Shelf Life	12 months
Standard Packing	20 litres

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.