

## MORSUN SYNTHETIC QUICK SETTING COPOLYMER VARNISH

**PRODUCT CODE****MCS-VR-627****PRODUCT DESCRIPTION**

Single pack Anti-corrosive Clear Varnishbased On Modified Synthetic Resin suitable for exterior use

**TECHNICAL DATA**

|                              |                                                                                                                                                                                                                                                                                    |
|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>SUGGESTED USES</b>        | An ideal coating to be used as a finish coat on a Variety of substrates, viz. Wood, Ferrous and Non-Ferrous substrates. The cured film provides highly transparent hard, flexible, abrasion and stain resistant coating which has excellent anti-corrosive property and durability |
| <b>Colour</b>                | Clear                                                                                                                                                                                                                                                                              |
| <b>Finish</b>                | Glossy                                                                                                                                                                                                                                                                             |
| <b>Volume Solids</b>         | 45%+2                                                                                                                                                                                                                                                                              |
| <b>Weight Solids</b>         | 48%+2                                                                                                                                                                                                                                                                              |
| <b>Mixing Ratio</b>          | Single Pack                                                                                                                                                                                                                                                                        |
| <b>Recommended dft</b>       | 20-25μ                                                                                                                                                                                                                                                                             |
| <b>Theoretical Covering</b>  | 18.0M2 at 20μ                                                                                                                                                                                                                                                                      |
| <b>Method of Application</b> | Brush/Roller/Conventional spray                                                                                                                                                                                                                                                    |
| <b>Thinner Recommended</b>   | Not Recommended                                                                                                                                                                                                                                                                    |
| <b>Drying Time</b>           | Handleable in 10-15 Minutes and hard dries also fast, subject to ambient temperature and DFT. Lower DFT gives faster DRYING                                                                                                                                                        |
| <b>Surface Preparation</b>   | Ensure application is carried out on a clean and dry surface free of all contaminants viz. oil, grease, rust, dust, etc                                                                                                                                                            |
| <b>Shelf Life</b>            | 12 months in sealed container stored at room temperature                                                                                                                                                                                                                           |
| <b>Packing</b>               | 20litres, 4litres                                                                                                                                                                                                                                                                  |
| <b>Precautions</b>           | Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area. Store this Varnish under roof in cool & well-ventilated room                                                                                                                  |

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.