

MORSUN EXTERIOR WATER BASED EMULSION PRIMER

PRODUCT CODE

MCS-WB-952

PRODUCT DESCRIPTION

A superior quality water-based acrylic polymer Emulsion primer designed as an exterior application for walls on dry and humid climate conditions. It is ready to use, ease in application, fast drying and improves top coat adhesion. It has good adhesion, coverage, opacity with excellent water resistant. It is an alkali resistant primer to exterior emulsion paint

SUGGESTED USES

Exterior Acrylic polymer-based emulsion is high quality primer to be applied on exterior walls of houses, architectural buildings in dry or moderately humid climatic condition

TECHNICAL DATA

Colour	White / All Shades
Finish	Smooth Matt
Flash Point	Not Applicable
Recommended dft	25-35 µm
Theoretical Covering	10.0 M2 at 30 µm DFT /Ltr/Coat
Method of Application	Brush and Roller and Conventional spray
Dilution	15-25 % by volume with clean, potable water
Clean up solvent	Clean, potable water
Drying Time	Surface Dry : 25-30 Minutes
Tach Free	50-60 Minutes
Hard Dry	4-6 hours
Overcoating Interval	2-3 hours Minimum
Recommended Application System	1 Coat water based Exterior Emulsion primer 2-3- Coat water based Exterior Emulsion Paint
Shelf Life	24 months in sealed container stored at room temperature
Packing	20 litres, 4 litres
Precautions	Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.