

MORSUN EXTERIOR WATER BASED EMULSION PAINT

PRODUCT CODE

MCS-WB-953

PRODUCT DESCRIPTION

A superior quality water based Acrylic Emulsion paint is specially designed for exterior application at dry and humid climate condition. It has good opacity, coverage, high durability, excellent recoatability with smooth finish and resistance to algae and fungal and also non-yellowing properties

SUGGESTED USES

Water based Exterior Acrylic emulsion paint specially designed to apply on Exterior wall of houses, architectural buildings in dry or moderately humid climatic condition

TECHNICAL DATA

Colour	White / All Shades
Finish	Smooth Matt
Flash Point	Not Applicable
Recommended dft	25-30 µm
Theoretical Covering	10.20 M2 at 30 µm DFT /Ltr/Coat
Method of Application	Brush and Roller and Conventional spray
Dilution	10-15 % by volume with clean, potable water
Clean up solvent	Clean, potable water
Drying Time	Surface Dry : 25-30 Minutes
Tack Free	50-60 Minutes
Hard Dry	4-6 hours
Overcoating Interval	2-4 hours Minimum
Recommended Application System	1 Coat water based Exterior Emulsion Primer 2 Coat water based Exterior Emulsion Paint
Shelf Life	24 months in sealed container stored at room temperature
Packing	20 litres, 4 litres
Precautions	Surface should not have Water seepage. Do not apply on Damp surface. Do not apply while raining. Avoid inhalation. Take necessary precautions to avoid contact with skin or eyes. Ventilate the area

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.