

MORSUN ETCHING PRIMER

PRODUCT CODE

MCS-WP-001

PRODUCT DESCRIPTION

A Two pack pre-treatment primer used for etching metal surfaces known to be difficult for paint adhesion. It provides a sound base for the subsequent coating system. It is used mainly on aluminium, tin, chromium and cadmium plating, nickel, copper, brass and galvanised surfaces and also on re-bars and steel surfaces. It is also sometimes used on plastic sheets and resin laminates to enhance adhesion

TECHNICAL DATA

Colour	Yellow/Green
Finish	Matt
Flash Point	> - 4°C
Mixing Ratio	2 : 1 or 1 : 1
Volume Solids	10% + 2
Recommended DFT	6 - 8μ
Theoretical Covering	12.5 M ² per litre @ 8μ
With 20% Loss	8.75 M ²
Drying Time	Touch Dry : 15 minutes
Hard Dry	2 hours
Interval before Coating	24 hours
Mode of application	Brush / Spray
Shelf Life	6 months
Surface Preparation	Surface should be clean & dry free from all contaminants. Surface may be cleaned by blasting or by manual /mechanical methods
Precautions	DFT should not exceed 10 microns. Coating as such must not be exposed to weather or wetted with water. It may be left exposed for a maximum of 24 hours before overcoating in dry condition only
Safety	Since Flash Point very low store this material under shade well ventilated

Disclaimer: The information provided herein is derived from the best available sources and is given in good faith. As conditions of use are beyond our control, the Company gives no warranty, expressed or implied, and assumes no liability in connection with any use of this information.